





*No installation engineer needed

KEY FEATURES

Parts Counter Stroke adjustment **Micro Registration Index Speed Set up Stepper Motor Indexer** Adjustable stroke length **Squeegee Angle Adjustment** Parts Sensor (no product no print) **Adjustable Stroke and flood speed** Print Accuracy of .001" | 0.02mm **High-Density Flash Cure Units Pneumatic Screen Locks Color Touch Screen Curing Time Set up Hoodie arms**

Add-ons + Pallet: Sleeve, Face-Mask, Gloves, etc. + Laser guidance to assist positioning + Foot Pedal Unloader This machine can be adapted for various applications ★ Indicate Pallet size, Standard, or Max. print size * Also possible is Frame Size 9" x 20" | 22.8 x 50.8cm

SPECIFICATION

Height: 55" | 140cm **Diameter: 38" | 97cm**

8x Stations 2x Print Heads

Dwell set up

3x High-Density Flash Cure Units Print/Flash/Print/Flash/Flash

*Standard Pallet Size 4" Wide x 8 " Long | 10 cm x 20 cm Max Image Print Area 6" Wide x 6" Long | 15 cm x 15 cm

*Standard Frame Size 9" x 14" | 22.8 cm x 35.5 cm

Flash cure size: 5" x 5" | 12.7cm x 12.7cm

220 Volt Single Phase 25 Amps

